

नाशिक महानगरपालिका, नाशिक

सार्वजनिक आरोग्य विभाग

ई - कोटेशन नोटीस क्र. २४

दि.

१०/०२/२०२२

निम्नलिखित तपशीलाप्रमाणे नाशिक महानगरपालिका, नाशिक कार्यक्षेत्रात सार्वजनिक आरोग्य विभागांतर्गत कार्यान्वित एकात्मिक आरोग्य व कुटुंब कल्याण सोसायटी अंतर्गत जेडीसी बिटको येथील नवीन विशेष नवजात शिशु काळजी कक्ष उपकरणे खरेदी करणेकामी ई कोटेशन मागविण्यात येत आहे.

कोटेशन फॉर्म कालावधी : १०/०२/२०२२

कोटेशन भरून देण्याची अंतिम तारीख : १८/०२/२०२२

कोटेशन फॉर्म जमा करण्याचे ठिकाण व वेळ : ३ रा मजला, सार्वजनिक आरोग्य विभाग,  
राजीव गांधी भवन, शरणपुररोड, नाशिक.  
वेळ : सकाळी १० ते ५.४५ पर्यंत

वरील कामाचे कोटेशन पत्रक (अटीशर्तीसह) [www.nashikcorporation.in](http://www.nashikcorporation.in) या संकेत स्थळावर दिनांक १०/०२/२०२२ ते दिनांक १८/०२/२०२२ या कालावधीत उपलब्ध आहे.

कोटेशन जमा करण्याचे ठिकाण :- कोटेशन फॉर्म पूर्ण भरून ३ रा मजला, सार्वजनिक आरोग्य विभाग, राजीवगांधी भवन, शरणपुर रोड, नाशिक येथे कार्यालयीन वेळेत (सकाळी १० ते ५.४५ पर्यंत) देण्यात यावे. अपूर्ण कोटेशन स्विकारले जाणार नाहीत. मुदतीनंतर प्राप्त झालेले कोटेशन पाकिट स्विकारले जाणार नाही. कोटेशन फॉर्म स्विकारण्याचा अथवा नाकारण्याचा हक्क राखून ठेवण्यात येत आहे.

नोंद - आवश्यकते मालातील संख्येमध्ये घट किंवा वाढ होऊ शकते.

Sd/-

वैद्यकिय आरोग्य अधिकारी  
नाशिक महानगरपालिका, नाशिक

On letter Head

तपशिलाप्रमाणे नाशिक महानगरपालिका सार्वजनिक आरोग्य विभाग एकात्मिक आरोग्य व कुटुंब कल्याण समिती, राष्ट्रीय शहरी आरोग्य अभियान (एन.यु.एच.एम) अंतर्गत जेडीसी बिटको येथील नवीन विशेष नवजात शिशु काळजी कक्ष उपकरणे मी/आम्ही पुढीलप्रमाणे सर्व करांसह दर सादर करीत आहोत.

करणेकामी खालीलप्रमाणे नमुद बाजार भाव ई कोटेशन नोटिस प्रसिध्द करुन कोटेशन (दरपत्रके) सादर करण्यात येत आहे.

SR NO	NAME OF EQUIPMENT	Specification	Quantity	Price per unit	Total Amount (Inclusive all taxes)
1	OXYGEN HOOD -S AND M,SET OF 3 EACH , INCLUDING CONNECTING TUBES	Oxygen Hood - 1.oxygen hood-Transparent polycarbonate unbreakable single molded. 2. Round shape. 3.trauma free silicone neck Adjustment flap the wastage of oxygen. 4.Silicon rubber neck port adjustment ensures can be used Neonate/infant/pediatric patient’s. 5.Bilateral Oxygen nozzle prevents direct flow of cold Oxygen on patient’s head. 6.Hight:7.5”. 7.Width:8.5”. Oxygen inlet port with tubing. Warranty-1 Year.	6		
2	RESUSCITATOR,HAND OPERATED NEONATE,250 ML	Ambus Bag- Child model 250 ml – Manual resuscitator with transparent face-mask. 1. Usage/Application -hospital 2.material –self inflating resuscitator bag should be medical grade Silicone rubber. 3.Parts- Mask, inbuilt reservoir valve, side oxygen inlet. 4 Autoclavable.5 Should be single hand operatable. Warranty-1 Year.	2		
3	RESUSCITATOR,HAND OPERATED NEONATE, 500 ML LA	Ambus Bag- Child model 500 ml – Manual resuscitator with transparent face-mask. 1. Usage/Application -hospital 2.material –self inflating resuscitator bag should be medical grade Silicone rubber. 3.Parts- Mask, inbuilt reservoir valve, side oxygen inlet. 4 Autoclavable.5 Should be single hand operatable. Warranty-1 Year.	4		
4	LARYNGOSCOPE SET,NEONATE	Laryngoscope-Large hollow, cylindrical, slightly ribbed handle. Handle made of either chromium- plated or Stainless steel Can be opened to insert two batteries (type LR 14,Size C,1.5V) Stud contact, fitting various Sizes and types of depressors with a set of two stainless steel depressors, with halogen bulb Miller type: Straight NR 0, length approximately 70 mm Straight NR1, length approximately 100mm. Autoclavable. Warranty-3 Years. Bulb up to 6 months.	6		

5	SUCTION PUMP- FOOD OPERATED	.Suction pump-foot operated Surgical suction unit meets the requirements of all surgical fields of applications. The suction unit runs on oil free rocking piston vacuum pump and thermally protected vacuum pump motor. The unit having fiber cabinet. The suction unit is provided with autocavable/unbreakable collection jar made form high quality polycarbonate material. The collection jar have self sealing rubber lids. Vacuum can be adjusted with the help of vaccum regulator and vaccum gauge. Safety float prevents entry of suction fluid in the pump in case of overfilling. A special bacteria ensures zero contamination and thus prevents infection. Specification Vacuum 600mm of Hg Capacity 18LPM Power 40 watts Noise Level ≤64dB Power supply 220/230 V AC Collection Jars 1.5 Liters*2 Nos Mains Cable 2.5 Meters Exhaust Fan Yes Dimensions(mm) Length* Width *height- 300* 225* 300. Warranty-3 Years.	2		
6	SURGICAL INSTRUMENT/SUTUR E SET	Suture Set Kit, 3 Surgical Instruments Combo - 5’’ Adson Dissecting, 4’’ Iris Scissor and 6’’ Needle Holder Stainless Steel with Kitbag	2		
7	DIGITAL THERMOMETER	Measurement Range:32°C(89.6°F)----- 42°C(89°6F) · Low Temperature Display: Temperature43°C(109°4F)DisplayH°C(H°F) · Accuracy:35°C(95°F)----- 39°C(102.2°F)±0.1°C(0.2°F) · Display Resolution:0.1°C(0.1°F)	12		
8	ELECTRONIC WEIGHING SCALE FOR BABY, 10KG<5G>	Electronic weighing Scale for Baby ,15 kg,: Weighing range:0-15 kg● Minimum graduation : 5g.● Accuracy :±5g.● Display in kilograms● Functions : automatic Switch- off,TARE,HOLD,auto-calibration with switch on.● Large LCD diplay● Reading time max 5 Seconds● Splash proof and shock resistant light-weight body● Smooth surface/finishing for easy cleaning/disinfection.● All vital parts made of rust proof ,child-friendly materials;display cover made of● durable,transparent plastic. Power Requiurements:220V/50Hz● Additonal power supply:Custmor replacable batteries.Warrenty- 1 Year.	4		
9	STETHSCOPE FOR NEONATES- BINAURAL,	Mechanical stethoscope,chromium plated metal binaural,v rubber tube in one piece.rotating piper fitting for oth flip functions.Diaphragm approx.20 mm. Accessories-1 x spare set of earpiece,1x spare diapharmWarranty 1 Year.	12		

10	ELECTRONIC SPHYGMOMANOMETER FOR NEONATES	Accurate result detected by oscillograph One touch Operation Display Pulse, Systolic Pressure, Diastolic Pressure Irregular heartbeat detection (IHD) Automatic power –off to help extend battery life A Large LCD screen display WHO BP classification indicator Average of the last three measurement Batteries 4of size AA. Warranty-1 Year.	6		
11	ELECTRONIC MOBILE LIGHT EXAMINATION MOBILE (220-12V)	Electric Mobile Light/ examination mobile Light (220-12V): Number of LED 12 Intensity 35,000 Lux Diameter of Light 200mm Spot Diameter 100-150mm Depth Lumination 10-15cm Colour Temp. 4350K Colour Rendering index 91Ra LED Average Life >50000Hrs. Intensity Control 10-100 Digital Touch Power Supply 220V/50Hz AC Power Consumption 12 Watt.Waranty-1 Year.	6		
12	SYRING HUB CUTTER	Syringe hub cutter-portable and electrical-Rust resistant ·electro melting principle-Manually operated · Accurate performance · Capable destroying syringe with along neddles · Fine finish · Compact design.warranty-1 Year.	2		
13	VINYL-COATEDMEASURING TAPE ,1.5M.	Vinyl-coated Measuring tape , 1.5m.: Tape measure,vinyl-coated, fiberglass,with metal tips at both ends,graduated in centimeters. Dimensions: Length:1.5m. Width : minimum 1.3cm. Thickness: minimum 0.36mm	2		
14	BASIN,KIDNEY TRAY-STAINLESS STEEL,825ML	Basin, kidney tray – stainless steel, 825ml : Container,kidney shaped, kidney dish, stainless steel, smooth surface. Materials : Austenitic stainless steel composition :18 to 20% chromium,8 to 10% nickel. Length :240-260mm. Width : 130-150mm. Height :30-50mm. Capacity :800 to 850ml. Thickness :0.75-0.85mm. Warranty-1 Year	4		
15	DRESSING TRAY-STAINLESS STEEL 300*200*30mm	Dressing Tray-stainless steel, 300*200*30mm: Tray, dressing, stainless steel, 300×200×30 mm. Seamless tray, rectangular with rounded corners, stainless smooth surface Materials: Austenitic stainless steel;composition :18 to 20% chromium, 8 to 10 % nickel. Length :285-315mm. Width :190-220mm. Height :28 to 32mm. Thickness :0.75-0.85mm.Warranty-1 Year	4		

16	INFUSION STAND WITH DOUBLE HOOK CASTORS	<p>Infusion stand with double hook on castors: Movable height adjustable infusion stand. Heavy carriage mounted on 5 swivel castors. Lower – end support column is deep and securely fixed into the carriage-base. Solid manual lever at the upper-end of the support column, allows setting telescopic upper Part at the required height . A break prevents exceeding the maximum height setting. Double hook fixed at the top of telescopic rod. Material High resistance to corrosion (tropical environment) Support and telescopic column: Austenitic stainless steel 18/10. Carriage – base: single molded unit, polypropylene. Castor frame/bracket : polypropylene or nylon Wheel bearing:polypropylene or nylon Castor fixation into carriage base: Stainless steel.Warranty-1 Year</p>	3		
17	IFANFTOMETER PLEXI 3 ½ FT /105CM	<p>Infantometer-portable board must designed to measure length of baby in recumbent position-width- approx.30cmxlength 100cm.weight-approx 1 kg.material of board-ABS Material make.thickness of board-6mm.foldable.no sharp edges and corners.antiskid feature.</p>	1		
18	STERLIZING DRUM- 165MM DIAMETER	<p>Cylindrial containor used to sterilise dressing materials (gauze compress or cotton etc.) in a steam sterilizer (autoclave) and to keep them us “sterile” dressing materials for medical activities (i.e dressing, injection etc) Drum should have an effective closing lid with a clip lock , a carrying handle,air vents system to allow steam to circulate freely during the sterilisation cycle. Vents to be manually closed after sterilisation. Air vent system(opening and closure mechanism) must be efficient and easy to operate.Lateral air vents system is preferable to top and bottom air vents. Material: Austenitic stainless steel, smooth surface. Austenitic stainless steel composition: approx.8 to 10% nickel,18 to 20 % chromium. External diameter :approximately 150 to 165 mm. Height :approximately 100 to 120mm. Thickness : approximately 0.6 to 0.7.mm.Warranty-1 Year.</p>	1		

19	GLUCOMETER WITH DEXTOSTIX	Weight 0.2lbs(75g) Dimensions 3.6 in x2.3 inx0.9in(91mmx58mmx23mm) Data storage 400 glucose measurements or QC tests Measurements Range and units U.S. 10-900mg/dL Outside U.S. 1-50mmol/L Blood Glucose Measurement Sample volume required 1.2uL time to glucose results 6 seconds Connectivity Data transfer Data program Strip port coonection to USB Nova Microsoft –Excel best data transfer software Battery information Type 3v Li Button Battery Feature Replaceable life Minimum 600tests before battery requires replacement. Waranty-1 Year	3		
20	GOWNS	autoclavable,cotton gowns.green-hospital gowns	12		
21	SYRINGE PUMP 10,20,50 ML SINGLE PHASE	Syringe Pump 10,20,50ml single phase: Having Features Suitable for Cardiothoracic Patients Rugged and strong design for rough use Compact (2.4 Ltr) & Light Weight (1.75 Kg) 0.1 to 1200 ml/hr flow rate Long Battery Back-up up to 10 Hrs Dosage Ramp up and tapper down function Custom Programmable to accept any brand of syringe Auto Purge Bolus Facility Multiple Safety Alarm Facility Inline Program during infusion. Warranty-1 Year.	3		
22	OXYGEN CONCENTRATOR	Features: LED display panel for confortable view. Compact design ,light weight . 24/7 continious stable performance.One-button easy control · Accurate alarm system · Ideal products for medical and household use Specification: · Flow rate : 1-5L/min · Oxygen purity :90%±3% · Weight:15.5KG · Size:345*280*558mm · Outlet pressure: 0.02-0.07Mpa · Power consumption: 400w · Power supply: 220V/50HZ or 110V/60Hz · Noise: ≤54dB(A) · Nebulizing rate: ≥0.1ml/min · Alarm function: low purity,low pressure,power failure, overheat.Warranty-1 Year.	4		

### अटी/शर्ती

- १) सदरचे साहित्य मनपा ३ रा मजला,सार्वजनिक आरोग्य विभाग, राजीव गांधी भवन, शरणपुर रोड, किंवा आदेशात नमुद केल्या ठिकाणी पोहोच करावे लागेल. त्यासाठी वेगळा वाहतुक खर्च देण्यात येणार नाही.
- २) सदरचे दरपत्रकात सर्व करासह दर नमुद करावयाचे आहेत. कोणत्याही कराची जबाबदारी नाशिक महानगरपालिकेवर राहणार नाही.
- ३) कोणतेही कोटेशन स्विकारणे अगर नाकारण्याचा अधिकार निम्नस्वाक्षरीकार यांचा राहील.
- ४) आवश्यकते मालातील संख्येमध्ये घट किंवा वाढ होऊ शकते.
- ५) पुरवठादारास माल पुरविल्यानंतर देय कमीत कमी ७ दिवसाच्या आत PFMSद्वारे ऑनलाईन पध्दतीने पुरविलेल्या बँक खात्यात वर्ग करणेत येईल.

सदर कोटेशनसोबत असलेल्या सर्व अटी व शर्ती मी वाचले असुन मला त्या मान्य आहेत. सदर अटी शर्ती प्रमाणे सदर कोटेशनमध्ये नमुद केलेल्या दराने १२ महिने कालावधीकरीता पुरवठा करण्यास मी तयार आहे. त्यासाठी या कोटेशनवर स्वाक्षरी करीत आहे.

दिनांक :- / / .

कोटेशनधारकाची सही व शिक्का